

Bridgeport Spaulding Community School

Drainage System Maintenance

Overview

As a consequence of its function, the stormwater conveyance system collects and transports urban runoff that may contain certain pollutants. Maintaining catch basins, detention basins / retention basins, vegetated swales, rain gardens, stormwater inlets, and other stormwater conveyance structures on a regular basis will remove pollutants, prevent clogging of the downstream conveyance system, restore catch basins' sediment trapping capacity, and ensure the system functions properly hydraulically to avoid flooding. To ensure proper maintenance and effectiveness of these drainage systems, please review and apply the following approaches, protocols, and requirements below. This procedure requires that all controls be maintained to reduce to the maximum extent practicable the contribution of pollutants to stormwater. This maintenance standard operating procedure shall be reviewed and updated/revised annually following the implementation of a new structural storm water control. This standard operating procedure shall be reviewed and updated/revised by either the Bridgeport Spaulding Community School's appointed Stormwater Program Manager and/or the School's designee. Any updates will be included in future progress reports submitted to the Michigan Department of Environment, Great Lakes, and Energy (EGLE).

Procedures

Catch Basins and Storm Drain Conveyance System

- Will be inspected during the dry season (summer).
- Will be inspected according to Catch Basin Prioritization Procedures.
- High priority catch basins will be inspected in every year.
- Medium priority catch basins will be inspected every 2 years
- Low priority catch basins will be inspected every 5 years.
- The condition of the catch basin at the time of the inspection will be documented.
- Catch basins that have sediment within 18 inches of the pipe invert or half full will be cleaned within 90 days by a contractor.
- The contractor will use a vac truck when the catch basins are accessible to vac trucks.
- Catch basins are considered clean when the remaining material is not more than 2 inches in depth.
- The total amount of waste/sediment removed annually from the catch basins will be documented and included in progress reports.
- Waste materials from catch basin and storm sewer line cleaning will not be stored at Bridgeport Spaulding Community School properties. The contractor will dispose of all waste materials removed from catch basins and storm sewer lines immediately to an approved disposal area.
- The contractor will dispose of waste materials according to the Department of Environment, Great Lakes, and Energy disposal guidelines for catch basins.

(http://www.michigan.gov/documents/deq/wb-stormwater-CatchBasinGuidance_216198_7.pdf)

- The inventory of catch basins will be updated annually to include new structures. prior to discharging to surface waters of the state.

Measurable Goals

- Volume of sediment removed from the system per year.
- Volume of trash removed from the system per year.
- Number of structures cleaned or maintained per year.